

Application of analytical pyrolysis for the molecular fingerprinting of polymers (PE, PET, PP, PS and PVC) within natural organic matter matrices used for rooftop farming

Medina Veliu, Joeri Kaal, Asier Goñi-Urtiaga, Tiago De Oliveira, Giuseppe Picca, Eduardo Moreno-Jiménez, Johnny Gasperi, Denis Courtier-Murias, Liliane Jean-Soro, Marco Panettieri

▶ To cite this version:

Medina Veliu, Joeri Kaal, Asier Goñi-Urtiaga, Tiago De Oliveira, Giuseppe Picca, et al.. Application of analytical pyrolysis for the molecular fingerprinting of polymers (PE, PET, PP, PS and PVC) within natural organic matter matrices used for rooftop farming. Suitma 12th Conference on Soils of Urban, Industrial, Traffic, Mining and Military Areas, Sep 2023, Santiago de Compostela, Spain. . hal-04134050

HAL Id: hal-04134050 https://univ-eiffel.hal.science/hal-04134050

Submitted on 15 Sep 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



12thConference on Soils of Urban, Industrial, **Traffic, Mining and Military Areas** Santiago de Compostela, September 4th - 7th, 2023





Figure

Py-GC-MS

pyrograms of pure Jiffy

peat (orange) and PS 1%

mixture in Jiffy peat

(black) (A); pyrograms of

styrene trimer peak

(10.8 min) in non-treated

JPS1 (B) and in JPS1


oxidized for 24 hours (C)

and 48 hours (D).


Application of analytical pyrolysis for the molecular fingerprinting of polymers (PE, PET, PP, PS and PVC) within natural organic matter matrices used for rooftop farming


Medina Veliu (1,2), Joeri Kaal (2,3), Asier Goñi-Urtiaga (2), Tiago De Oliveira (1), Giuseppe Picca (2), Eduardo Moreno-Jiménez (4), Johnny Gasperi (1), Denis Courtier-Murias (1), Liliane Jean-Soro (1), Marco Panettieri (2) (1) Univ Gustave Eiffel, GERS-LEE, F-44344 Bouguenais, France; (2) Instituto de Ciencias Agrarias (ICA), CSIC, Serrano 115 b, 28006 Madrid, Spain; (3) Pyrolyscience S.L.U., 15706 Santiago de Compostela, Spain; (4) Department of Agricultural and Food Chemistry, Faculty of Sciences, Universidad Autónoma de Madrid, Madrid, Spain

INTRODUCTION



MATERIALS AND METHODS





—JPS1_549_ug

12

Retention Time (min)

JPS1 48h H2O2 30%

—JPS148_1st_m_3_518ug

 H_2O_2 30% oxidation at 45°C for 24 h and 48 h on Jiffy peat + PS 1% (JPS1)

RESULTS

Pyrolysis products proportions in mixtures of synthetic polymers and natural organic matter





Figure 1. Balance between plastics concentration in the mixtures of synthetic polymers and natural organic matter (x-axis, log scale) and the proportions of the peak areas for Py-GC-MS (left) and THM-GC-MS (right). (Kaal et al. 2023, Under review)



Detection limits for synthetic polymers in peat matrix with

- Py-GC-MS: 0.01% (PS), 0.02% (PET), 2% (PE, PP, PVC)
- THM-GC-MS: 0.02% (PET), 0.2% (PP), 2% (PE, PVC)

NO linear trend with dose rate

PS stability was expressed as styrene trimer/dimer ratio: values are comparable before and after oxidation (JPS1: 3.2 ± 0.5 ; JPS124: 3.5 ± 1.5).

¥. 20 ⊈. 15

CONCLUSIONS

• OM fingerprinting approach can be used to identify SyOM when present in significant amounts (0.01-2% depending on the polymer)

Selected PS characteristic peaks (styrene monomer, dimer and trimer) more abundant after

• Oxidation with H₂O₂ 30% enhances PS molecular fragment peaks in JPS1 pyrograms

PERSPECTIVES

- Detection limits of synthetic polymers in peat samples after H₂O₂ oxidation
- Application of oxidation protocol and Py-GC-MS analysis to composts of urban rooftop




Retention Time

oxidation treatment. Improved detection limits?

JPS1 24h H₂O₂ 30%

—JPS124_2nd_g_3_540ug



REFERENCES

Under review)

• Bouzid, N. et al. 2022. Quantification of microplastics by pyrolysis coupled with gas chromatography and mass spectrometry in sediments: Challenges and implications. Microplastics 1, 229–239

Figure 2. Summary of Py-GC-MS and THM-GC-MS data for the five synthetic polymers in NOM matrix. (Kaal et al. 2023,

- Kaal, J., Goñi-Urtiaga, A., Wenig, P., Veliu, M., Moreno-Jiménez, E., Plaza, C., Panettieri, M. 2023. Simultaneous molecular fingerprinting of natural organic matter and synthetic polymers (PE, PET, PP, PS and PVC) using analytical pyrolysis. Journal of Analytical and Applied Pyrolysis. UNDER REVIEW
- Fischer, M. et al. 2017. Simultaneous trace identification and quantification of common types of microplastics in environmental samples by pyrolysis-gas chromatography-mass spectrometry. Environ Sci Technol., 51, 5052-5060.
- Pérez-Rodríguez, M. et al. 2023. Explicit microrelief-controlled decoupling of initial aerobic (in hummocks) and anaerobic (in hollows) decay in superficial layers of Sphagnum-dominated peatlands.
- Picca, G. et al. 2023. Suitability of co-composted biochar with spent coffee grounds substrate for tomato (Solanum lycopersicum) fruiting stage. Horticulturae 9, 89.

CLEAR DOC

contact: medina.veliu@univ-eiffel.fr