



**HAL**  
open science

# An Efficient Algorithm for $K$ -Diagnosability Analysis of Bounded and Unbounded Petri Nets

A Chouchane, M Ghazel

► **To cite this version:**

A Chouchane, M Ghazel. An Efficient Algorithm for  $K$  -Diagnosability Analysis of Bounded and Unbounded Petri Nets. WODES'2024 - 17th IFAC Workshop on Discrete Event Systems, Apr 2024, Rio de Janeiro, Brazil. hal-04578239v1

**HAL Id: hal-04578239**

**<https://univ-eiffel.hal.science/hal-04578239v1>**

Submitted on 16 May 2024 (v1), last revised 6 Jun 2024 (v2)

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# An Efficient Algorithm for $K$ -Diagnosability Analysis of Bounded and Unbounded Petri Nets <sup>★</sup>

A. Chouchane\*, M. Ghazel\*

\* *COSYS-ESTAS, Univ. Gustave Eiffel, Lille Campus, F-59650, Villeneuve d'Ascq, France (e-mail: chouchanea41@gmail.com, mohamed.ghazel@univ-eiffel.fr).*

---

**Abstract:** In this paper, we propose a polynomial algorithm for conducting  $K$ -diagnosability analysis on both bounded and unbounded labeled Petri nets. More specifically, we formulate a sufficient condition for  $K$ -diagnosability by addressing the relaxation (in  $\mathbb{R}$ ) of an Integer Linear Programming (ILP) problem defined on a compacted horizon. In addition, if the model is  $K$ -diagnosable, the technique provides a value  $K_{relax}$ , potentially lower than  $K$ , that ensures ( $K_{relax}$ -)diagnosability. To assess the performance and efficiency of the developed method, a Petri net model of a railway benchmark is investigated.

*Keywords:*  $K$ -diagnosability, bounded and unbounded labeled Petri nets, discrete event systems, linear optimization technique.

---

## 1. INTRODUCTION AND RELATED WORKS

In this paper, our focus is on investigating the  $K$ -diagnosability of Discrete Event Systems (DES) modeled by a partially observed Labeled Petri Net (LPN).  $K$ -diagnosability refers to the ability to diagnose any fault with certainty, provided that at least  $K$  events have occurred following the fault occurrence ( $K \in \mathbb{N}$ ). In fact,  $K$ -diagnosability can be of particular interest in practice, since, in some applications, the delay required for detecting and identifying fault occurrences may have considerable impact in terms of safety and/or performance.

In a recent work Chouchane et al. (2023), we have investigated the  $K/K_{min}$ -diagnosability problems in bounded and unbounded LPNs, while assuming the unobservable subnet to be acyclic. The main contribution lies in the development of a necessary and sufficient condition for  $K$ -diagnosability, which can be checked by means of ILP optimization techniques. Besides, if the investigated fault class is  $K$ -diagnosable, the minimum value  $K_{min} \leq K$  ensuring  $K_{min}$ -diagnosability is also provided by the same analysis, without requiring further investigation. Furthermore, the parameter  $J$  introduced in this methodology (distinct from the one defined in Basile et al. (2012)), which serves to characterize the set of faulty sequences that are relevant to the examination of  $K$ -diagnosability, enabled an expansion of the approach proposed in Basile et al. (2012) to address the case of unbounded nets.

The present work is, in fact, an extension of the approach established in Chouchane et al. (2023). In fact, using algebraic techniques offers crucial advantages in terms of efficiency compared to *graph-based* approaches (Liu et al. (2017); Cabasino et al. (2012)), since algebraic techniques (Basile et al. (2012, 2015); Zhu et al. (2021))

do not require building the state space of the net. Yet, addressing ILP problems can entail significant computational costs. Specifically, these problems are NP-hard, and their solving complexity grows exponentially with the number of variables, in the worst case (Boccia et al. (2020); Lancia and Serafini (2021)). Our goal here is to improve the computational complexity of the approach in Chouchane et al. (2023), while dispensing from the determination of parameter  $J$ . Namely, we propose a new algorithm for  $K$ -diagnosability analysis, in a compacted horizon, based on the relaxation of an ILP problem (in  $\mathbb{R}$ ). Using a compacted horizon not only reduces the system's dimensionality but also eliminates the need for parameter  $J$ , which could be difficult to determine in an optimal way. The technique we discuss in the present paper provides a sufficient condition for  $K$ -diagnosability. Moreover, when the established (sufficient) condition is fulfilled, a value  $K_{relax}$  is given such that the fault class is  $K_{relax}$ -diagnosable where  $K_{min} \leq K_{relax} \leq K$ .

The structure of the paper is outlined as follows. In Section 2, we introduce some essential preliminary concepts and highlight key findings from Chouchane et al. (2023), focusing on  $K$ -diagnosability using ILP problems. Section 3 explores the relaxation of the ILP problem in  $\mathbb{R}$  and establishes a sufficient condition for  $K$ -diagnosability. Section 4 illustrates the developed technique on the basis of a railway Petri Net model, while demonstrating the effectiveness of our technique. Finally, in Section 5, we conclude the paper and present potential directions for future research.

## 2. PRELIMINARIES

### 2.1 Notations

A Petri net, denoted as  $\mathcal{N} = (P, T, W^-, W^+)$ , is defined by sets  $P$  and  $T$ , representing non-empty finite sets of places

---

<sup>★</sup> This paper was not presented at any IFAC meeting.

and transitions, respectively. The pre-incidence matrix is denoted as  $W^-$  and the post-incidence matrix as  $W^+$ . The incidence matrix  $W$  is calculated as  $W = W^+ - W^-$ .

The marking of a place  $p$  is denoted as  $M(p)$ . A marked Petri net is represented as  $(\mathcal{N}, M_0)$ , where  $M_0$  is the known initial marking. The notation  $M [ t >$  signifies a transition  $t$  enabled by marking  $M$  if  $M(p) \geq W^-(p, t)$  for all places  $p \in P$ . The term  $M [ t > M'$  indicates that marking  $M'$  is reachable from marking  $M$  by firing transition  $t$  ( $M' = M + W(\cdot, t)$ ). The reachability set of  $(\mathcal{N}, M_0)$  is denoted as  $R(\mathcal{N}, M_0)$ . The language of the net is represented by  $L(\mathcal{N}, M_0) = \{\sigma \in T^* \mid \exists M \in R(\mathcal{N}, M_0) : M_0 [\sigma > M]\}$ .

The notation  $\pi_T(\sigma)$  refers to the *count vector* associated with sequence  $\sigma \in T^*$  where the  $i^{\text{th}}$  element of vector  $\pi_T(\sigma)$  represents the number of firings of transition  $t_i$  in  $\sigma$ . The set  $T_o$  represents observable transitions, while  $T_u$  denotes unobservable ones.  $P_o(\sigma)$  and  $P_u(\sigma)$  correspond to the projection of  $\sigma$  on  $T_o^*$ , and  $T_u^*$ , respectively. The function  $\pi_{T_o} : T_o^* \rightarrow \mathbb{N}^{|T_o|}$  restricts the application of function  $\pi_T$  to observable sequences and, similarly,  $\pi_{T_u} : T_u^* \rightarrow \mathbb{N}^{|T_u|}$  restricts it to the set of unobservable sequences. The observable subnet of Petri Net  $\mathcal{N}$  is denoted as  $\mathcal{N}_o = (P, T_o, W_o^-, W_o^+)$ , with  $W_o^- = W^-|_{T_o}$ , and  $W_o^+ = W^+|_{T_o}$ . Similarly, the unobservable subnet is denoted as  $\mathcal{N}_u = (P, T_u, W_u^-, W_u^+)$ , with  $W_u^- = W^-|_{T_u}$ , and  $W_u^+ = W^+|_{T_u}$ .

The *labeling function*, denoted as  $\mathcal{L} : T \rightarrow E \cup \{\varepsilon\}$ , assigns to each transition  $t \in T$  either a label in  $E$  if  $t \in T_o$ , or  $\varepsilon$  if  $t \in T_u$ . An LPN system, represented as  $\mathcal{N}_{\mathcal{L}} = (\mathcal{N}, M_0, E, \mathcal{L})$ , consists of a Petri net  $\mathcal{N}$  with a known initial marking  $M_0$  and a finite set of events  $E$  that are assigned to its transitions as labels, by means of the labelling function  $\mathcal{L}$ . The extension of  $\mathcal{L}$  to transition sequences is denoted as  $\mathcal{L} : T^* \rightarrow \{E \cup \{\varepsilon\}\}^*$ . The projection of  $\sigma \in T^*$  in the set of observable labels  $E^*$  is denoted by  $P_l(\sigma)$  and is defined as  $P_l(\sigma) = \mathcal{L}(P_o(\sigma))$ . The inverse projection operator, denoted as  $P_l^{-1}(w)$ ,  $w \in E^*$ , is defined as:  $P_l^{-1}(w) = \{\sigma \in T^* \mid P_l(\sigma) = w\}$ . Function  $\pi_E : E^* \rightarrow \mathbb{N}^{|E|}$  assigns to any word  $w \in E^*$  a vector  $y = \pi_E(w) \in \mathbb{N}^{|E|}$ , where each component  $\pi_E(w)^i$ ,  $1 \leq i \leq |E|$ , corresponds to the number of occurrences of the  $i^{\text{th}}$  label in  $E$  within  $w$ . The set of sequences that enable fault class  $T_f$  for the first time is defined as  $\psi(T_f) = \{\sigma \in T^* \mid (T_f \notin \sigma) \wedge (\exists \varepsilon_f \in T_f : M_0[\sigma \varepsilon_f >])\}$ .

## 2.2 LPN structure

In the considered LPN, the set of transitions is partitioned as  $T = T_o \uplus T_u$ , where  $T_o$  (resp.  $T_u$ ) is the set of observable (resp. unobservable) transitions. The set of unobservable transitions is, in turn, partitioned into two disjoint subsets  $T_u = T_f \uplus T_{reg}$ , where  $T_f$  corresponds to the set of fault transitions while  $T_{reg}$  corresponds to the regular (*i.e.*, non-faulty) unobservable transitions. Furthermore, the set of fault transitions  $T_f$  can be partitioned into  $r$  disjoint subsets ( $T_f = \bigcup_{i=1}^r F_i$ ) that represent the different fault classes. Without loss of generality and for the sake of clarity, one single fault class ( $T_f$ ), is considered in this paper. A sequence  $\sigma \in T^*$  is said to be faulty if it contains at least one fault transition of  $T_f$  (*i.e.*,  $\exists \varepsilon_f \in T_f$  such that  $\varepsilon_f \in \sigma$ ). In the remainder of the paper, we say that

*fault class  $T_f$  occurred* to mean that some fault transition  $\varepsilon_f \in T_f$  has fired.

In this paper, for  $K$ -diagnosability analysis, we consider the following assumptions:

**H0)** the considered LPN does not reach a deadlock after firing any fault transition, and

**H1)** the unobservable subnet is acyclic.

## 2.3 $K/K_{min}$ -diagnosability of an LPN

**Definition 1.** ( *$K$ -diagnosability of a fault class*) A fault class  $T_f$  in an LPN is  $K$ -diagnosable for some given integer  $K \in \mathbb{N}^*$ , if the following holds:

$$(\forall \sigma_{bf} \in \psi(T_f)) (\forall \sigma_{af} | M_0[\sigma_{bf} \varepsilon_f \sigma_{af} > ; \varepsilon_f \in T_f] : |\sigma_{af}| \geq K \Rightarrow \text{Diag})$$

where the diagnosability condition is defined as:

$$\text{Diag} : \sigma \in P_l^{-1}[P_l(\sigma_{bf} \sigma_{af})] \Rightarrow T_f \in \sigma.$$

A corollary problem arises in the case when  $K$ -diagnosability is confirmed. Namely, it consists to determine a minimum value  $K_{min} \leq K$  that ensures ( $K_{min}$ -)diagnosability.

## 2.4 Algebraic approach for $K/K_{min}$ -diagnosability analysis in Chouchane et al. (2023)

In the present paper, we build upon our work discussed in Chouchane et al. (2023), which addresses  $K$  and  $K_{min}$ -diagnosability in LPNs.

### A. Principle.

The principle of the approach is as follows: *Given an LPN and a fault class  $T_f$ , the  $K/K_{min}$ -diagnosability analysis problem can be rephrased as follows: is there  $K_{min} \leq K$  such that  $T_f$  is  $K_{min}$ -diagnosable and  $T_f$  is not  $(K_{min} - 1)$ -diagnosable? If so,  $T_f$  is  $K_{min}$ -diagnosable and therefore  $K$ -diagnosable.*

To determine  $K_{min}$ , we proceed as follows: we assume that there exists some value  $\kappa$ ,  $1 \leq \kappa \leq K$ , such that  $T_f$  is not  $\kappa$ -diagnosable. Hence, we determine the maximum value of  $\kappa$ , denoted as  $\kappa_{max}$  (if it does exist) such that there exit two feasible firing sequences  $\sigma, \sigma' \in T^*$  fulfilling the following condition denoted as  $C_{\sigma-\sigma'}(\kappa)$ :

$$C_{\sigma-\sigma'}(\kappa) : \begin{cases} \sigma = \sigma_{bf} \varepsilon_f \sigma_{af}, \sigma_{bf} \in \psi(T_f), \varepsilon_f \in T_f, \\ |\sigma_{af}| = \kappa; \\ T_f \notin \sigma'; \\ P_l(\sigma) = P_l(\sigma'). \end{cases}$$

Therefore, the following verdict can be inferred:

- If  $\nexists \kappa$  verifying  $C_{\sigma-\sigma'}(\kappa)$ , then  $K_{min} = 1$ .
- If  $1 \leq \kappa_{max} < K$  then  $K_{min} = \kappa_{max} + 1$ .
- If  $\kappa_{max} = K$  then  $T_f$  is not  $K$ -diagnosable.

### B. Algebraic model.

In Chouchane et al. (2023), in order to establish a necessary and sufficient condition for  $K$ -diagnosability, an algebraic model is developed for formulating sequences  $\sigma$  and  $\sigma'$  that satisfy condition  $C_{\sigma-\sigma'}(\kappa)$  for some value  $\kappa$ ,  $1 \leq \kappa \leq K$ . To achieve this goal, it is essential to characterize the length of the sequences within  $\psi(T_f)$ , *i.e.*, which enable fault class  $T_f$  for the first time, without the need to explicitly determine the entire set. In Chouchane et al. (2023), a necessary and sufficient condition for

$K$ -diagnosability was established for bounded and unbounded LPNs using ILP techniques. The main idea of the technique developed in Chouchane et al. (2023) will be summarized in what follows, so that the contribution developed in the present paper be self-contained. Note that, similarly to the work in Basile et al. (2012) and the recent approach in Basile et al. (2023) discussing initial state opacity analysis, in Chouchane et al. (2023) we considered the following assumption:

**H2)** A sufficient maximal length  $J$  of the prefixes that activate fault class  $T_f$ , for the first time, is known.

### Modeling the faulty sequence:

Let us assume that fault class  $T_f$  is  $K_{min}$ -diagnosable with  $K_{min} > 1$ , then there exists at least one firable sequence  $\sigma = \sigma_{bf}\varepsilon_f\sigma_{af}$  from  $M_0$  such that:

- $\sigma_{bf} = t^{<1>}t^{<2>} \dots t^{<J>}$  with  $t^{<i>} \in (T \setminus T_f) \cup \{\zeta\}$  for all  $i \in \llbracket 1, J \rrbracket$ , where  $\zeta$  stands for the empty step sequence;
- $\varepsilon_f = t^{<J+1>} \in T_f$ ;
- $\sigma_{af} = t^{<J+2>} \dots t^{<J+K_{min}>}$  with  $t^{<i>} \in T$  for all  $i \in \llbracket J+2, J+K_{min} \rrbracket$ ; and
- there exists at least one fault-free sequence  $\sigma' \in (T \setminus T_f)^*$  enabled from  $M_0$ , such that  $P_l(\sigma) = P_l(\sigma')$ .

In fact, since  $K_{min} \leq K$  is not known a priori, we expand the firing sequence  $\sigma_{af}$  over horizon  $J+K+1$  by taking  $t^{<J+K_{min}+1>} \dots t^{<J+K+1>}$  as empty step sequences in case  $K_{min} < K$ . Therefore, we can write  $\sigma = t^{<1>}t^{<2>} \dots t^{<J+K+1>}$ , where for  $i \in \llbracket 1, J+K+1 \rrbracket$   $t^{<i>}$  may correspond to an observable transition, an unobservable transition or even the empty step sequence  $\zeta$ .

We denote by  $x_o^{<i>} = \pi_{T_o}(t^{<i>})$  and  $x_u^{<i>} = \pi_{T_u}(t^{<i>})$ , yielding  $x^{<i>} = [(x_o^{<i>})^\top (x_u^{<i>})^\top]^\top$ . Consequently, we get the following set of constraints:

$$\left\{ \begin{array}{l} W^- \cdot x^{<1>} \leq M_0 \\ -W \cdot \sum_{i=1}^{j-1} x^{<i>} + W^- \cdot x^{<j>} \leq M_0; \forall j \in \llbracket 2, J+K+1 \rrbracket \quad (a) \\ 0 \leq c \cdot x^{<j>} \leq 1, \forall j \in \llbracket 1, J+K+1 \rrbracket \quad (b) \\ \sum_{i=1}^J c_f \cdot x^{<i>} = 0 \quad (c)^{(1)} \\ c_f \cdot x^{<J+1>} = 1 \quad (d) \\ c \cdot x^{<j>} - c \cdot x^{<j+1>}, \forall j \in \llbracket J+2, J+K \rrbracket \quad (e) \\ 1 \leq \sum_{i=J+2}^{J+K+1} c \cdot x^{<i>} \leq K \quad (f) \end{array} \right. \quad \left\{ \begin{array}{l} -W_u \cdot x_u^{<1>} + W_o^- \cdot x_o^{<1>} \leq M_0 \\ -W_u \cdot \sum_{i=1}^j x_u^{<i>} - W_o \cdot \sum_{i=1}^{j-1} x_o^{<i>} + W_o^- \cdot x_o^{<j>} \quad (f) \\ \leq M_0; \forall j \in \llbracket 2, J+K+1 \rrbracket \\ \sum_{i=1}^{J+K+1} c_f \cdot x^{<i>} = 0 \quad (g) \end{array} \right. \quad (2)$$

where  $c$  is a row vector of 1's of dimension  $|T|$  and  $c_f$  is a row vector of dimension  $|T|$ , of which all the elements are null, except the elements that are associated with fault transitions in  $T_f$ , which are equal to 1.

Constraints (a) arise from the firing conditions of transitions  $t^{<1>} \dots t^{<J+K+1>}$  respectively. Constraints (b) stipulate that, during each iteration  $<j>$  from  $<1>$  to  $<J+K+1>$ , no more than one transition can be fired. Constraint (c) ensures that no fault transition of fault class  $T_f$  occurs from iteration  $<1>$  to iteration  $<J>$ . Constraint (d) specifies that the initial appearance of a fault transition in  $T_f$  takes place at the  $(J+1)^{th}$  iteration. Constraints (e) dictate that, within iterations  $<J+2>$

to  $<J+K+1>$ , the count vector remains at 1 until the  $<J+K_{min}+1>^{th}$  iteration, where it irrevocably switches to 0 and stays at 0 until the final iteration  $<J+K+1>$ . Constraint (f) stipulates that the faulty sequence  $\sigma$  includes a minimum of one transition and a maximum of  $K$  transitions after the first occurrence of the fault class.

**Remark 1.** Under **H0**, system (1) is satisfied iff there exists a feasible faulty sequence  $\sigma$  with a maximum of  $K$  transition firings upon the first occurrence of fault class  $T_f$ . In fact, (1) corresponds to the state equation that describes a faulty sequence  $\sigma$  (with  $|\sigma| \leq J+K+1$ ), accounting for at most one transition firing per iteration (Theorem 3 in Chouchane et al. (2023)).

### Modeling the fault-free sequence

Now that faulty sequence  $\sigma$  has been formally defined, let us assume the existence of a corresponding non-faulty indistinguishable sequence (w.r.t.  $T_f$ )  $\sigma'$ , such that  $P_l(\sigma) = P_l(\sigma') = w$ . Given that  $\sigma$  comprises at most  $J+K+1$  transitions, we can deduce that  $|w| \leq J+K+1$ . Hence, we can represent  $w$  as  $w = l^{<1>}l^{<2>} \dots l^{<J+K+1>}$ , where  $l^{<i>}$  denotes the label produced at iteration  $<i>$ , which may be either a label in  $E$  or the empty step label. Let  $\sigma'_o = P_o(\sigma')$ , and let  $\sigma'_u$  as  $\sigma'_u = t'_o^{<1>}t'_o^{<2>} \dots t'_o^{<J+K+1>}$  where  $t'_o^{<i>} \in \mathcal{L}^{-1}(l^{<i>})$  if  $l^{<i>} \in E$ , and the empty sequence otherwise. Consider the unobservable sequences (explanations)  $\sigma'_u^{<1>} \dots \sigma'_u^{<J+K+1>}$  that are coherent with transitions  $t'_o^{<1>} \dots t'_o^{<J+K+1>}$ , respectively. The firing count vector of the fault-free sequence  $\sigma'$  can then be written as  $\sigma' = \sigma'_u^{<1>}t'_o^{<1>} \sigma'_u^{<2>}t'_o^{<2>} \dots \sigma'_u^{<J+K+1>}t'_o^{<J+K+1>}$ .

Let  $x^{<i>} = ((x_o^{<i>})^\top (x_u^{<i>})^\top)^\top$  be the firing count vector of  $\sigma'_u^{<i>}t'_o^{<i>}$  where  $x_o^{<i>} = \pi_{T_o}(t'_o^{<i>})$  and  $x_u^{<i>} = \pi_{T_u}(\sigma'_u^{<i>})$ . The following set of constraints can therefore be derived:

Constraints (f) stem from the firing conditions, while constraint (g) dictates that sequence  $\theta$  must be devoid of any fault transitions.

**Remark 2.** Under hypotheses **H0** and **H1**, equation (2) is satisfied if and only if there exists some feasible fault-free sequence  $\sigma'$ . In fact, in a PN with an acyclic unobservable subnet, every positive solution of state equation  $M = M_0 + W \cdot x$  corresponds to a count vector of an actual feasible firing sequence (Theorem 1 in Chouchane et al. (2023)).

Let us now establish the relationship between  $x_o^{<i>}$  and  $y^{<i>}$ ,  $i \in \llbracket 1, J \rrbracket$  where  $y^{<i>}$  represents the count vector of the observed label associated with the  $i^{th}$  iteration. To achieve this, let us consider the arrangement of  $T_o$  and  $E$  as  $\{t_1, \dots, t_{|T_o|}\}$  and  $\{\ell_1, \dots, \ell_{|E|}\}$ , respectively. Let  $\wp \in \{0, 1\}^{|E| \times |T_o|}$  be the labeling matrix, where the general term  $\wp_{qr}$  is defined as follows for  $q \in \llbracket 1, |T_o| \rrbracket$  and  $r \in \llbracket 1, |E| \rrbracket$ :



while  $x'^{<J+1>}, \dots, x'^{<J+K+1>}$  remain unchanged. The model of fault-free sequence  $\sigma'$  under horizon compression satisfies the following constraints:

$$\left\{ \begin{array}{l} -W_u \cdot x_u'^{<1 \rightarrow J>} + W_o^- \cdot x_o'^{<1 \rightarrow J>} - W_u \cdot x_u'^{<J+1>} + \\ \quad W_o^- \cdot x_o'^{<J+1>} \leq M_0 \\ -W_u \cdot x_u'^{<1 \rightarrow J>} + W_o^- \cdot x_o'^{<1 \rightarrow J>} - W_u \cdot \sum_{i=J+1}^j x_u'^{<i>} - W_o \cdot \\ \quad \sum_{i=J+1}^{j-1} x_o'^{<i>} + W_o^- \cdot x_o'^{<j>} \leq M_0; \forall j \in \llbracket J+2, J+K+1 \rrbracket \\ c_f \cdot x_u'^{<1 \rightarrow J>} + \sum_{i=J+1}^{J+K+1} c_f \cdot x_u'^{<i>} = 0 \\ \varphi \cdot x_o'^{<1 \rightarrow J>} = \varphi \cdot x_o'^{<1 \rightarrow J>} \\ \varphi \cdot x_o'^{<i>} = \varphi \cdot x_o'^{<i>} ; \forall i \in \llbracket J+1, J+K+1 \rrbracket \end{array} \right. \quad (10)$$

### C. Final model.

According to (8) and (10), if there exists a couple of sequences  $(\sigma, \sigma') \in C(\kappa)$  where  $1 \leq \kappa \leq K$  under hypothesis **H0** and **H1**, then there exists a couple of corresponding count vectors  $(X, X') \in \mathbb{N}^{(2+K) \cdot |T|} \times \mathbb{N}^{(2+K) \cdot |T|}$  that fulfills the following relation:

$$A_c \cdot \begin{pmatrix} X_c \\ X'_c \end{pmatrix} \leq b_c \quad (11)$$

where  $A_c$  and  $b_c$  can be easily deduced.

### 3.2 Main results

Let us consider the following optimization problem:

$$\left\{ \begin{array}{l} \max_{\mathbb{N}} (\lambda_c^\top \cdot X_c) \\ A_c \cdot \begin{pmatrix} X_c \\ X'_c \end{pmatrix} \leq b_c; X_c, X'_c \in \mathbb{N}^{(2+K) \cdot |T|} \end{array} \right. \quad (12)$$

with  $\lambda = (\mathbf{0}_{1 \times 2 \cdot |T|} \mid c \ c \ \dots \ c)^\top \in \mathbb{N}^{(2+K) \cdot |T|}$  and  $c$  is as defined in (1). The relaxation of ILP problem (12) can be defined as follows:

$$\left\{ \begin{array}{l} \max_{\mathbb{R}} \lambda_c^\top \cdot X_c \\ A_c \cdot \begin{pmatrix} X_c \\ X'_c \end{pmatrix} \leq b_c; X_c, X'_c \geq \mathbf{0}; X_c, X'_c \in \mathbb{R}^{(K+2) \cdot |T|} \end{array} \right. \quad (13)$$

The relaxed model (13) neglects the integer nature of the count vectors. At this stage, the objective is to establish a sufficient condition for  $K$ -diagnosability based on system (13), and determine a value  $K_{relax} \leq K$  that ensures  $K_{relax}$ -diagnosability. First, let us recall the following lemma that establishes the relation between the cost functions respectively of an ILP problem and its corresponding relaxed problem. It should be noted that for  $x \in \mathbb{R}$ ,  $\lfloor x \rfloor$  denotes the integer part of  $x$ .

**Lemma 2.** (Liao and Devadas (1997)).

Let  $\{\max_{\mathbb{Z}}(c^\top \cdot x) \mid A \cdot x \leq b\}$  and  $\{\max_{\mathbb{R}}(c^\top \cdot x) \mid A \cdot x \leq b\}$  be respectively the cost functions of an ILP problem and its relaxation in  $\mathbb{R}$ . Therefore,  $\max_{\mathbb{R}}(c^\top \cdot x) \geq \lfloor \max_{\mathbb{Z}}(c^\top \cdot x) \rfloor \geq \max_{\mathbb{Z}}(c^\top \cdot x)$ .

From Lemma 2 and considering both optimization problems (12) and (13), we can state that:

$$\max_{\mathbb{R}}(\lambda_c^\top \cdot X_c) \geq \lfloor \max_{\mathbb{R}}(\lambda_c^\top \cdot X_c) \rfloor \geq \max_{\mathbb{N}}(\lambda_c^\top \cdot X_c) \quad (14)$$

Using relation (14), the following sufficient condition for  $K$ -diagnosability can be established based on (13).

**Theorem 3.** Consider an LPN that fulfills assumptions **H0** and **H1** and consider some fault class  $T_f$ . For a fixed  $K \in \mathbb{N}^*$ ,  $T_f$  is  $K$ -diagnosable if either of the following two conditions is fulfilled:

-i- (13) has no solution, or

-ii- (13) admits a solution in  $\mathbb{R}$  and  $\max_{\mathbb{R}}(\lambda_c^\top \cdot X_c) < K$

**Proof.** i- (13) has no solution in  $\mathbb{R}$  implies that (12) has no solution in  $\mathbb{N}$ . Therefore, (7) has no solution either. Thus, according to Theorem 1 and Corollary 1,  $T_f$  is  $K$ -diagnosable and in particular 1-diagnosable.

ii- If (13) admits a solution and  $\max_{\mathbb{R}}(\lambda_c^\top \cdot X_c) < K$ , then according to (14), for  $\kappa = \lfloor \max_{\mathbb{R}}(\lambda_c^\top \cdot X_c) \rfloor + 1 \leq K$ , there

does not exist any pair of vectors  $(X_c, X'_c)$  satisfying (11).

In other terms, for  $\kappa = \lfloor \max_{\mathbb{R}}(\lambda_c^\top \cdot X_c) \rfloor + 1 \leq K$ , there

does not exist any pair  $(\sigma, \sigma') \in C(\kappa)$  and hence  $T_f$  is  $K_{relax}$ -diagnosable with  $K_{relax} = \lfloor \max_{\mathbb{R}}(\lambda_c^\top \cdot X_c) \rfloor + 1 \leq K$ .

Obviously,  $T_f$  is  $K$ -diagnosable.

**Corollary 2.** If the sufficient condition stated in proposition 3 holds, then we can conclude not only that  $T_f$  is  $K$ -diagnosable but also that it is  $K_{relax}$ -diagnosable with:

-  $K_{relax} = 1$  if (13) has no solution,

-  $K_{relax} = \lfloor \max_{\mathbb{R}}(\lambda_c^\top \cdot X_c) \rfloor + 1$  if  $\max_{\mathbb{R}}(\lambda_c^\top \cdot X_c) < K$  in (13).

We can also state that:

$$K_{min} \leq K_{relax} \leq K \quad (15)$$

**Remark 3.** The  $K$ -diagnosability test, as well as the determination of a potentially lower value  $K_{relax} \leq K$  (in case  $K$ -diagnosability is fulfilled), can be performed in a polynomial time in  $2|T|(K+2) \times (K+2) \cdot (2|P| + 2|T| + |E| + 3) + 5$ . Indeed, some linear programming algorithms of polynomial complexity are available, such as, for instance, the Karmarkar algorithm Karmarkar (1984).

## 4. EXPERIMENTAL RESULTS

In this section, we conduct experiments to assess the efficiency of the discussed technique. We employ the railway benchmark proposed in Ghazel and Liu (2016), addressing a level crossing system that encompasses  $n$  railway tracks (where  $n$  is a variable). To experimentally evaluate the developed technique and compare it with the ILP-based approaches for  $K$ -diagnosability analysis, defined in Chouchane et al. (2023) and Basile et al. (2012), we implemented a Matlab<sup>®</sup> code for the approach discussed in the current paper, and used to Matlab code of the techniques in Chouchane et al. (2023) and Basile et al. (2012). The experiments were conducted on a dual-core Intel(R) Xeon(R) CPU with a clock speed of 3.30 GHz each and 32 GB of RAM. We set the value of  $K$  to 125 and assessed the  $K$ -diagnosability of fault transition  $t_6$  while varying the number of tracks  $n$  from 1 to 18, thereby increasing the model size. It should be noted that only the approaches in Chouchane et al. (2023) and Basile et al. (2012) require parameter  $J$ . The results are showcased in

